

# IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application Serial No. . . . . Unknown  
 Filing Date . . . . . December 4, 2000  
 Inventor . . . . . Charles H. Dennison  
 Assignee . . . . . Micron Technology, Inc.  
 Group Art Unit . . . . . Unknown  
 Examiner . . . . . Unknown  
 Attorney's Docket No. . . . . MI22-1577  
 Title: Field Effect Transistors, Integrated Circuitry, Methods of Forming Field  
 Effect Transistor Gates, and Methods of Forming Integrated Circuitry

## PRELIMINARY AMENDMENT

To: Box Patent Application  
 Assistant Commissioner for Patents  
 Washington, D.C. 20231  
  
 From: Mark S. Matkin (Tel. 509-624-4276; Fax 509-838-3424)  
 Wells, St. John, Roberts, Gregory & Matkin P.S.  
 601 West First Avenue, Suite 1300  
 Spokane, WA 99201-3828

Please enter the following amendments prior to examining the above-identified application.

## AMENDMENTS

### In the Specification

At p. 1 before the "Technical Field" section, please insert the following:

### --RELATED PATENT DATA

This patent resulted from a continuation application of U.S. Patent Application Serial No. 09/138,150, filed August 21, 2000, entitled "Field Effect

Transistors, Integrated Circuitry, Methods of Forming Field Effect Transistor Gates, and Methods of Forming Integrated Circuitry", naming Charles H. Dennison as inventor, the disclosure of which is incorporated by reference.--

### **In the Claims**

Cancel claims 1-56

Add claims 57-116 as follows:

57. A field effect transistor comprising:

a pair of source/drain regions having a channel region positioned therebetween; and

a gate positioned operatively proximate the channel region, the gate comprising semiconductive material conductively doped with at least one of a p-type or n-type conductivity enhancing impurity effective to render the semiconductive material electrically conductive, a silicide layer and a conductive diffusion barrier layer to diffusion of p-type or n-type conductivity enhancing impurity, the conductive diffusion barrier layer comprising  $TiW_xN_y$ .

58. The transistor of claim 57 wherein the conductive diffusion barrier layer comprises  $W_xN_y$ .

59. The transistor of claim 57 wherein the conductive diffusion barrier layer comprises  $\text{TiO}_x\text{N}_y$ .

60. The transistor of claim 57 wherein the conductive diffusion barrier layer is formed over the silicide layer.

61. The transistor of claim 57 wherein the silicide layer is formed over the conductive diffusion barrier layer.

62. Integrated circuitry comprising:

a field effect transistor including a gate, a gate dielectric layer, source/drain regions and a channel region; the gate comprising semiconductive material conductively doped with a conductivity enhancing impurity of a first type and a conductive diffusion barrier layer to diffusion of first or second type conductivity enhancing impurity; and

insulative material received proximate the gate, the insulative material including semiconductive material provided therein in electrical connection with the gate, the semiconductive material provided within the insulative material being conductively doped with a conductivity enhancing impurity of a second type, the conductive diffusion barrier layer of the gate being provided between the gate semiconductive material and the semiconductive material provided within the insulative material.

63. The integrated circuitry of claim 62 wherein the first type is n and the second type is p.

64. The integrated circuitry of claim 62 wherein the first type is p and the second type is n.

65. The integrated circuitry of claim 62 wherein the gate also comprises a conductive silicide.

66. The transistor of claim 65 wherein the silicide and the conductive diffusion barrier layer comprise the same metal.

67. The integrated circuitry of claim 62 wherein the semiconductive material within the insulating material contacts the conductive diffusion barrier layer of the gate.

68. The integrated circuitry of claim 62 wherein the semiconductive material within the insulating material does not contact the conductive diffusion barrier layer of the gate.

69. The integrated circuitry of claim 62 wherein the gate also comprises a conductive silicide, the semiconductive material within the insulating material contacting the silicide.

70. The integrated circuitry of claim 62 wherein the conductive diffusion barrier layer is received over the gate semiconductive material, and the semiconductive material within the insulating material is received over the gate.

71. The integrated circuitry of claim 62 wherein the insulative material comprises an opening within which the semiconductive material therein has been provided, the opening being substantially void of any conductive diffusion barrier layer material.

72. The transistor of claim 62 wherein the conductive diffusion barrier layer is selected from the group consisting of  $W_xN_y$ ,  $TiO_xN_y$ , and  $TiW_xN_y$ , and mixtures thereof.

73. The transistor of claim 72 wherein the conductive diffusion barrier layer comprises  $W_xN_y$ .

74. The transistor of claim 72 wherein the conductive diffusion barrier layer comprises  $\text{TiO}_x\text{N}_y$ .

75. The transistor of claim 72 wherein the conductive diffusion barrier layer comprises  $\text{TiW}_x\text{N}_y$ .

76. The transistor of claim 62 wherein the conductive diffusion barrier layer is formed over the silicide layer.

77. The transistor of claim 62 wherein the silicide layer is formed over the conductive diffusion barrier layer.


### REMARKS

Claims 1-56 are cancelled. Claims 57-77 are added. Claims 57 and 62-77 are the same as claims 1 and 16-56, respectively, of the parent application, U.S. Patent Application Serial No. 09/138,150, as allowed. This continuation application is being submitted out of an abundance of caution to have the allowed claims considered in light of art which was recently discovered by Applicant. Such art is cited in an accompanying Information Disclosure Statement.

Respectfully submitted,

Dated: 12-4-00

By:

  
Mark S. Matkin  
Reg. No. 32,268